

Low Power NTSC/PAL Video Decoder with Differential CVBS Inputs and MIPI-CSI2 Output Interface

TW9992

The [TW9992](#) is a low power NTSC/PAL analog video decoder that is designed for automotive applications. It supports single-ended, differential and pseudo differential composite video inputs. Integrated short-to-battery and short-to-ground detection, advanced image enhancement capabilities such as the programmable Automatic Contrast Adjustment (ACA) and the MIPI-CSI2 output interface make the TW9992 an ideal solution for demanding automotive camera applications.

Features

Analog Video Decoder

- Software selectable analog input control allows for combinations of single-ended CVBS, and differential CVBS
- Built-in analog anti-alias filter
- Two 10-bit ADCs and analog clamping circuit
- Fully programmable static gain or automatic gain control for the Y channel
- Programmable white peak control for the Y channel
- 4-H adaptive comb filter Y/C separation
- PAL delay line for color phase error correction
- Digital subcarrier PLL for accurate color decoding
- Digital horizontal PLL for synchronization processing and pixel sampling
- Advanced synchronization processing and sync detection for handling nonstandard and weak signal
- Automatic color control and color killer
- Chroma IF compensation
- VBI slicer supporting industrial standard data services
- VBI data passthrough, raw ADC data output
- Programmable output cropping

Video Processing

- Automatic Contrast Adjustment (ACA)
- RGB565
- Programmable hue, brightness, saturation, contrast and sharpness.
- Image enhancement with peaking and CTI

MIPI Output

- MIPI 1.1 compliant unidirectional output format
- YUV 422 or RGB565 output format

Digital Output

- Output voltage 1.8V to 3.3V with 3.3V tolerance

Miscellaneous

- Low power consumption: 100mW typical
- Power save and Power-down mode
- Short-to-battery detection test
- Short-to-ground detection test
- Two-wire MPU serial bus interface
- Supports real time control interface
- Single 27MHz crystal for all operations
- Supports 24.54MHz and 29.5MHz crystal for high resolution square pixel format decoding
- 3.3V tolerant I/O
- 1.8V/3.3V power supply
- 32 Ld QFN (WQFN with wettable flanks)
- TW9992AT-NA1-GE is [AEC-Q100](#) qualified




FIGURE 1. TW9992 FUNCTIONAL BLOCK DIAGRAM

For additional products, see www.intersil.com/en/products.html

Intersil products are manufactured, assembled and tested utilizing ISO9001 or TS16949 quality systems as applicable noted in the quality certifications found at www.intersil.com/en/support/qualandreliability.html

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Intersil:](#)

[TW9992-NA1-CE](#) [TW9992AT-NA1-GE](#)