

DCJ010


Silicon Epitaxial Planar Type Diode

High-Speed Switching Diode

Features

- · Rectifier applications.
- \cdot Ideally suited for use in hybrid ICs because of ultrasmall-sized package.
- · Small interterminal capacitance.


Electrical Connection



Package Dimensions

unit: mm

1246A





Absolute Maximum Ratings at Ta = 25 °C

Parameter	Symbol	Conditions	Ratings	Unit
Peak Reverse Voltage	V_{RM}		20	V
Reverse Voltage	V _R		20	V
Peak Forward Current	I _{FM}		200	mA
Average Rectified Current	lo		100	mA
Surge Current	I _{FSM}	(1 μs)	300	mA
Allowable Power Dissipation	Р	(Total)	100	mW
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		-55 to +125	°C

Electrical Characteristics Ta = 25 °C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	Offic
Forward Voltage	V _F	I _F =10 mA			1.0	V
Reverse Current	I _R	V _R =15 V			0.1	μΑ
Interterminal Capacitance	С	V _R =6 V, f=1 MHz			4.0	pF





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property lose.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibilty for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of May, 1997. Specifications and information herein are subject to change without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

DCJ010-TL-E