DBD10G

ON Semiconductor®

http://onsemi.com

ON Semicon


1.0A Single-Phase Bridge Rectifier

Features

· Plastic molded structure

Peak reverse voltage: VRM=600V
Average output current: IO=1.0A

Electrical Connection



Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Value	Unit
Peak Reverse Voltage	V _{RM}		600	V
Average Output Current	I _O	Ta=25°C	1.0	Α
Surge Forward Current	IFSM	50Hz sine wave, 1cycle	30	Α
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		-40 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Value			Linit
			min	typ	max	Unit
Forward Voltage	VF	I _F =0.5A			1.05	V
Reverse Current	IR	V _R =V _{RM}			10	μΑ
Thremal Resistance	Rth(j-l)	Junction-Lead			15	°C / W
Thremal Resistance	Rth(j-a)	Junction-Ambient			68	°C / W


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Package Dimensions

unit:mm(typ.)


Surface mount type (TM emboss taping)





ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.



Ordering Information

Device	Shipping	memo		
DBD10G-TM-E	1,000 pcs. / reel	Pb-Free		
DBD10G-E	70 pcs. / fnfld	Pb-Free		

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

DBD10G-E DBD10G-TM-E